

Algae

Percival® model AL-22L2

Standard SciWhite® LED lighting

SciBrite® LED lighting (optional)
shown in top compartment

Specifications, excluding exterior dimensions, are per compartment only.



Applications

- Designed for algae that require higher light intensity, short plants that require moderate light intensity and many more applications

Percival's IntellusUltra Controller

The IntellusUltra (C8) control system adapts to nearly any programming style with a large range of options for optimal control over experiments.

- Robust and reliable, industrial-grade integrated hardware design
- Highly flexible programming capabilities for customized configurations and expansion
- Precise, simultaneous control of up to 7 environmental parameters
- Industry-leading experiment protection and system diagnostics

IntellusUltra Touchscreen Interface

This high-resolution touchscreen displays advanced settings and data for fine-tuning experiments, including graphs and charts.

- 10.1" IPS, high resolution display with 10-point multi-touch sensitivity
- Tabular and graphical presentation of chamber programs and parameters
- Highly visible process values and alarm notifications
- Enhanced user feedback menus

Please visit www.percival-scientific.com for more information on our control systems.



SciWhite LED Lighting System

- Two tiers of SciWhite lighting (one on each shelf)
- Programming/real-time control through the IntellusUltra touchscreen
- Intensity up to 350 $\mu\text{moles/m}^2/\text{s}$ of light irradiance measured @ 6" from LEDs
- Dimmable output from 10-100% in one-percent increments

Airflow/Circulation

- Conditioned air circulates through a rear wall plenum and travels horizontally across each shelf; air then flows vertically upward through the space between the door and shelves back to the unit cooler

AL-22L2 specifications (subject to change without notice)

Temp Range with all lights on	Interior Space volume		Total Shelving Floor Area		Maximum Growing Height		Exterior Dimensions						Light Intensity 6" from lamps unless otherwise noted	Tiers
							width		depth		height			
°C	ft³	m³	ft²	m²	in	cm	in	cm	in	cm	in	cm	µmoles/m²/s	
7-44±0.5	14.6	0.4	10.8	1	8.8	22.4	33.5	85.1	36.6	93	77.9	197.8	350	2

Algae Percival model AL-22L2

Cabinet Construction

- Interior constructed of 22-gauge galvanized steel
- Interior floor constructed of 22-gauge polished stainless steel
- Exterior constructed of 18-gauge Galvannealed extra-smooth steel
- NSF-compliant seam design
- Overall wall thickness is 2" (5.1 cm)
- Integrated floor drain in each compartment
- Contains casters assembly and adjustable leveling legs
- One 1.25" access port with air-tight plug per compartment
- Highly durable and reflective white coating

Insulation

- Woodless construction using 2" foamed-in-place non-CFC Urethane insulation with 97% closed cell-structure density of 2.2 lbs/ft³

Door

- One door opening 29.3" x 27.8" (74.3 cm x 70.5 cm) provides full access to the chamber interior
- Magnetic gasket provides a tight seal to door frame
- Lift-off hinge design allows for simple removal of door

Interior Space

- 14.6 ft³ (0.4 m³) with work area of 10.8 ft² (1 m²) provided per compartment

Shelving

- Two tiers per compartment of white epoxy coated steel wire shelving (each shelf is 28.8"W x 27"D [73 cm x 68.6 cm])
- Shelves are supported by shelf clips allowing ½" vertical adjustments
- Maximum growing height is 8.8" (22.4 cm)

Refrigeration

- Twin condensing unit (continuous running condensing unit ensures precise temperature control by alternately cycling refrigerant and hot gas to coil; this also prolongs life of compressor and eliminates risk of ice buildup in coil)
- Extended stem solenoid valves for quiet and long life operation
- Heat rejection to the ambient (standard refrigeration system) = 2,650 BTU/hr

Temperature Range

- 7°-44°C (±0.5°C) lights on; 2°-44°C (±0.5°C) lights off

Temperature Safety Limit Controls

- Experiment protection (adjustable high/low temperature control, audible alarms and visual indicators)
- Controls shut down all power to the chamber, activating alarms
- System automatically resets when temperature returns to normal range

Humidity Control (optional)

- Ultrasonic humidifier with advanced RH sensor (H11)
- Ultrasonic humidifier and dehumidifier with advanced RH sensor (H12)
- Ultrasonic humidifier with electronic RH sensor (H14)
- Ultrasonic humidifier and dehumidifier with electronic RH sensor (H15)

See other specification sheets or contact Percival Scientific for additional information.

Options Per Compartment (most popular)

- IntellusUltra Connect (C9)
- Additive CO₂ control
- CO₂ removal system
- Self-contained water-cooled condensing unit
- Dry alarm contacts
- Closed loop dimmable lighting with PAR light sensor (Q22)
- Open loop dimmable lighting per tier (Q23+)
- Extended temperature ranges available
- Convenience receptacles

Contact info@percival-scientific.com for additional information.

Electrical Service Requirements

- 120/1/60 with NEMA 5-15P plug provided (with standard chamber)
- RLA=10.6, MCA=13.3

Regulatory Standards

- Electrical Safety: UL-508A, certified and labelled by Percival Scientific under UL file number E340161
- Quality System: ISO 9001:2015, certified under DQS, Inc. under certification number 10017261

Helping You Create Better Science

Percival Scientific controlled environment systems are the culmination of over 60 years of design and manufacturing experience. Our high quality products have been developed through direct partnerships with the scientific community and offer platforms that are highly customizable and provide superior performance. We understand that scientific innovation is bred through creativity, passion, technical expertise and attention to detail, and we are proud to help you create better science.



Percival Scientific, Inc.

505 Research Drive • Perry, IA 50220 USA

800.695.2743 • 515.465.9363 • Fax: 515.465.9464

www.percival-scientific.com